



“Small but for **great needs**”



Urban construction sites and limited work spaces are the ideal application for the BF 60.1 crusher bucket, regardless of the crushing job.

Suitable for excavators starting from 8 Ton, the BF60.1 weighs approximately 1,5 Ton and has a capacity of approx. 0.60 m³.

The mouth opening measures to 610x510 mm to ensure an optimal production rate of 19,80 m³/h.

AREAS OF APPLICATION

DEMOLITION
RECYCLING
EXCAVATION
ROAD WORKS

SPECIFICATIONS

RECOMMENDED EXCAVATOR	LOAD CAPACITY	OPENING DIMENSIONS	OUTPUT SETTING	DIMENSIONS
≥ 8 Ton	0,60 m ³	L 610 H 510 mm	≥ 15 mm ≤ 110 mm	1790 x 1000 H 1160 mm
OIL FLOW	PRESSURE	COUNTER PRESSURE	WEIGHT	MAXIMUM PRODUCTION
98 l	210 bar	10 bar	1,50 Ton	19,80 m ³ /h

ACCESSORIES

RECOMMENDED SPARE PARTS KIT	FIX COUPLER	QUICK FEMALE COUPLER	IRON SEPARATOR	MIST KIT
BF6010028	FC6010000	BF6010000	BF6010010	KNMB00L - KNMB00S
				24 MONTHS WARRANTY
				WA246010