



COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV
= ISO 9001 =



Company Certification
= UNI EN ISO 14001:2004 =
IN PROGRESS

“Handy with high performance”



Suitable for excavators between 9 to 20 Ton, specially designed for medium sized environments where applications require high level performance.

Ideal for use before or after crushing, the MB-S14 screening bucket will reduce crushing time up to 60%. The MB-S14 also allows the screening of natural material (quarry residues, dry soil, and river stone) of any kind, making it convenient for on-site processing.

A must in reducing volumes and optimizing the size of materials for specific uses

PRIMARY SELECTION:

- WASTE MATERIAL
- DEMOLITION MATERIAL
- EXCAVATION FILLING MATERIAL
- PEBBLES IN STREAMS
- DEBRIS IN BEACHES
- NATURAL STONES CLEANING

SPECIFICATIONS

RECOMMENDED EXCAVATOR	LOAD CAPACITY	BASKET DEPTH	GRID DIAMETER	DIMENSIONS
≥ 9 < 20 Ton	1,20 m ³	890 mm	1200 mm	1730 x 1400 H 1430 mm
OIL FLOW	PRESSURE	DRAIN (BAR)	WEIGHT	SPEED
60 l	230 bar	-	1,10 Ton	25 / 35 min / max

ACCESSORIES

RECOMMENDED SPARE PARTS KIT	FIXED COUPLER	QUICK FEMALE COUPLER
MBS120002	FC6010000 - FC7020000	BF6010000 - BF707020000

24 MONTHS WARRANTY

WA241400