Mobile flooring plants

CIFA O EASYFLOOR by SBLEND



A single solution for flooring



Easyfloor is a mobile plant for the production and pumping of:

SCREED

dry and semi-dry

SELF-LEVELING

SPRITZ dry and wet

DRAINING CONCRETE

MULCH (A70)

SOIL

GRAVEL

SAND

EXPANDED CLAY

Compact and rugged automotive design:

- Real-Time Embedded operating system
- Power supply voltage: 9 .. 32 Vdc
- Operating temperature: -30 .. +75 ° C
- Protection class: IP67
- Overcurrent protection
- Ready for WiFi, LTE and GPS



On board control panel with a simple and intuitive interface.

Integration MYBLEND system for:

- MONITORING SYSTEM
- REMOTE ASSISTANCE

TECHNICAL DATA	A 70	P 70
	6.150 mm	6.150 mm
Total required power	75 Kw PTO	85 Kw PTO
Pumping	3 ÷ 8 m3/h	5 ÷ 30 m3/h
Max pressure	6 bar	70 bar
Cycle per minute	-	30
Conc. cylinders (diam. x stroke)	-	176×660 mm
Aggregates	~14 m3	~14 m3
Cement	3.5 m3	3.5 m3
Water	2.000 L	2.000 L
Additive	2×42 L	2×42 L
Tube winder	60 m	50 m
Pumping height*	100 m	75 m
Pumping distance*	180 m	150 m
Equipment weight	~4 300 Kg	~4 800 Kg
Dimensions	6.150 x 2.250 x 2.276 mm	6.150 x 2.250 x 2.276 mm
Max grain size	12 mm	25 mm
Consistency	dry, semi-dry, wet	Plastic, self-leveling



Material Type	Grain size
Screed	12 mm max
Wet soil Self-leveling screed	
· ·	Carried Section



Material Type	Grain size
Concrete Self-leveling screed	25 mm max















ITALY

Via Castegnato, 19 - 25050 Rodengo Saiano - Brescia +39 0307689730 info@blendplants.com www.blendplants.com

ITALY

Via Stai Uniti d'America, 26 - 20030 Senago - Milano +39 02990131 sales@cifa.com www.cifa.com